

The EURO 46 is the ideal solution for your EN 50131-1 Grade 2 and 3 residential, commercial and industrial installations giving you the peace of mind that your customer's property is protected and complies with all the relevant standards. The EURO 46 is also suitable for domestic homes that require police response.

The user friendly interface is designed for quick and easy programming and the features available maximise false alarm prevention. Users can control their system with utmost simplicity with the proximity card, tag or pin code and benefit from intelligent setting features.

- Supports mixed End of Line and Double Pole wiring, which is ideal for upgrading existing systems
- Expandable to 46 inputs
- Selectable EOL resistor values
- Standard alarm cable can be used (daisy chain or star wired)
- 6 Areas (or part sets)
- 75 User codes
- Up to 40 programmable outputs
- Digi modem: Signals SMS, Contact ID & Fast Format protocols
- Full upload and download features including ARM® (Automated Remote Maintenance)
- ARM® service options allows automated service periods from 1 week to 1 year
- · On-board and remote calibrated diagnostics
- · Contemporary remote keypad with 32 characters, with in-built proximity reader, 2 inputs and extension speaker output/PGM loud speaker driver
- User friendly menu driven programming
- · Optional satin chrome, chrome or brass flushmount keypad
- · Optional internal and external proximity readers
- Integrated access / door entry control
- Available in small (250 x 297 x 82mm) and large (390 x 305 x 100mm) metal cases











EN 50131-1





